

// PRODUCT CATALOG 2026

Lighting, smart electrical & hardware.

OEM / ODM programs for importers and brands. 9 models · full parameter tables · MOQ & lead time.

Range overview

Lighting		Smart Electrical	Hardware	
KW-PL320, KW-CP260, KW-CL400, KW-LR1200		KW-SW86, KW-SM55	KW-HG316, KW-ST48, KW-HN934	
MODEL	PRODUCT	CATEGORY	MOQ	LEAD TIME
KW-PL320	Aluminium Dome Pendant	Lighting	200 pcs	25–35 days
KW-CP260	Industrial Cage Pendant	Lighting	200 pcs	25–35 days
KW-CL400	Round LED Ceiling Panel	Lighting	300 pcs	20–30 days
KW-LR1200	Linear Recessed LED Profile	Lighting	100 m	15–25 days
KW-SW86	Smart Touch Wall Switch	Smart Electrical	500 pcs	25–35 days
KW-SM55	Surface-Mount Switch Box	Smart Electrical	500 pcs	20–30 days
KW-HG316	Stainless Steel Hinge	Hardware	1,000 pcs	20–30 days
KW-ST48	Self-Tapping Screws	Hardware	50,000 pcs	15–25 days
KW-HN934	Hex Nuts & Washers	Hardware	100,000 pcs	15–25 days

All prices are quoted per program (quantity, finish, packaging, destination market). Compliance documentation can be discussed during quotation.



LIGHTING • KW-PL320

Aluminium Dome Pendant

Spun-aluminium dome pendant for hospitality and retail interiors. Powder-coated, OEM colours available.

MOQ 200 pcs Lead 25–35 days

Housing	Spun aluminium, powder-coated
Diameter	320 mm
Light source	E27 socket, max 60 W / LED retrofit
Input voltage	AC 100–240 V, 50/60 Hz
Cable	1.5 m textile cable, adjustable
IP rating	IP20 (indoor)
Net weight	1.2 kg
Finish options	Black, white, brass-tone, custom RAL
Packaging	Individual carton, 6 pcs / master carton



LIGHTING • KW-CP260

Industrial Cage Pendant

Glass dome with steel guard — a rugged look for bars, cafés and warehouse-style interiors.

MOQ 200 pcs Lead 25–35 days

Housing	Steel cage, glass diffuser
Diameter	260 mm
Light source	E27 socket, max 40 W / LED retrofit
Input voltage	AC 100–240 V, 50/60 Hz
Suspension	1.2 m chain, ceiling canopy included
IP rating	IP20 (indoor)
Net weight	1.6 kg
Finish options	Matte black, aged brass-tone
Packaging	Foam insert, 4 pcs / master carton



LIGHTING • KW-CL400

Round LED Ceiling Panel

Ultra-slim surface-mount LED ceiling light with a soft opal diffuser and wood-tone trim.

MOQ 300 pcs Lead 20–30 days

Power	24 W / 36 W
Diameter	400 mm, 55 mm profile
Luminous flux	2,200 / 3,300 lm (nominal)
CCT	3000 K / 4000 K / 6500 K or CCT-switchable
CRI	Ra ≥ 80 (Ra ≥ 90 option)
Input voltage	AC 220–240 V, 50/60 Hz
Driver	Isolated constant-current driver
Dimming	Non-dim / triac / 0–10 V options
IP rating	IP40



LIGHTING • KW-LR1200

Linear Recessed LED Profile

Aluminium linear profile for continuous light lines in offices, corridors and showrooms.

MOQ 100 m Lead 15–25 days

Profile	Extruded aluminium 6063, anodised
Length	600 / 1200 / 1500 mm, linkable
Power	18 W per metre
Luminous flux	1,600 lm/m (nominal)
CCT	3000 K / 4000 K
Beam angle	110°
Diffuser	Opal PMMA
Input voltage	DC 24 V
IP rating	IP20



SMART ELECTRICAL · KW-SW86

Smart Touch Wall Switch

Wi-Fi / Zigbee touch switch in a standard 86 mm plate. App and voice-assistant ready platforms.

MOQ 500 pcs Lead 25–35 days

Plate size	86 × 86 mm
Gangs	1 / 2 / 3 gang
Protocol	Wi-Fi 2.4 GHz or Zigbee 3.0
Rated voltage	AC 100–250 V, 50/60 Hz
Max load	600 W per gang (resistive)
Panel	Tempered glass, touch-sensitive
Neutral wire	Required / no-neutral version option
Colours	White, black, grey
Branding	Logo print & custom packaging (OEM)



SMART ELECTRICAL · KW-SM55

Surface-Mount Switch Box

Surface-mount switch and socket boxes for exposed conduit installs in industrial and loft interiors.

MOQ 500 pcs Lead 20–30 days

Body	PC/ABS, UV-stabilised
Configuration	1-gang switch / socket / combo
Rated current	10 A / 16 A
Rated voltage	AC 250 V
Conduit entry	20 mm knock-outs
IP rating	IP44 / IP55 options
Colours	White, grey, black
Mounting	Surface, screw-fixed
Packaging	Polybag + inner box, 50 pcs / carton



HARDWARE · KW-HG316

Stainless Steel Hinge

Heavy-duty polished stainless hinges for marine, furniture and cabinet hardware programs.

MOQ 1,000 pcs Lead 20–30 days

Material	Stainless steel 304 / 316
Finish	Mirror polish / brushed
Size range	50–150 mm
Thickness	2.0–3.0 mm
Pin	Fixed or removable
Process	Stamping, CNC finishing, polishing
Tolerance	±0.1 mm (typical)
Customisation	Drawing-based OEM / ODM
Packaging	Polybag, 100 pcs / carton



HARDWARE · KW-ST48

Self-Tapping Screws

Pan and countersunk self-tapping screws in zinc-plated or stainless finishes, bulk or retail-packed.

MOQ 50,000 pcs Lead 15–25 days

Material	Carbon steel C1022 / SS 410 / SS 304
Head type	Pan, countersunk, wafer
Drive	Phillips, Pozi, Torx
Diameter	ST2.9 – ST6.3
Length	6 – 100 mm
Surface	Zinc plated, black oxide, passivated
Standard	DIN 7981 / 7982 equivalent
Packaging	Bulk carton or retail boxes
Customisation	Special lengths & coatings on request



HARDWARE • KW-HN934

Hex Nuts & Washers

Hex nuts and flat washers machined to common metric standards for assembly and fastening kits.

MOQ 100,000 pcs Lead 15–25 days

Material	Carbon steel / SS 304 / SS 316
Thread	M3 – M24 metric
Standard	DIN 934 / DIN 125 equivalent
Property class	Grade 8 / A2-70 / A4-80
Surface	Zinc plated, HDG, plain
Process	Cold forging, tapping
Inspection	Thread gauge & dimensional check
Packaging	25 kg cartons or kit packs
Customisation	Mixed fastening kits (OEM)

Send your RFQ.

1. Shortlist models & quantities
2. Share target price & destination
3. Receive quotation & samples plan
4. Approve pre-production sample
5. Mass production & inspection

Online: b2b-demo-taiyi3.vercel.app — Get a Quote

This is a concept catalog.

Built by 简物仓 as a sample of the ¥2,980 外贸展示站 tier. Want a catalog and inquiry site like this for your factory? jianwucang.com/studio

Photography via Pexels (Pexels License): Daniel Smyth, Sergey Sergeev, Andrea Piacquadio, makafood, Tolga deniz Aran, Jakub Zerdzicki, Bimbim Sindu, Roman Odintsov, William Warby, Gawtham Vijayan and other Pexels contributors.